

WAND BARCODE READER



Built on the platform of the world's best-selling single-line laser scanner, Honeywell's Voyager® 1200g delivers aggressive scan performance on virtually all linear bar codes, including poor quality and damaged codes. Updated object detection, and automatic in-stand detection and configuration enable class-leading presentation scanning that maximizes throughput. Superior scan performance matched with a reliable design combine to provide a versatile linear scanning solution suitable for a wide variety of applications.

Features

- Outstanding Scan Performance
- Class-Leading Presentation Scanning
- Multi-Interface
- Superior Out-of-Box Experience
- Contemporary, Ergonomic Design
- CodeGate® Technology

Mechanical

Dimensions (LxWxH) 66 mm (3.0") X 180 mm (7.1") X 97 mm (3.8")

Electrical

Input Voltage 5 V +/- 5%
Operating Power 700mW; 140 mA (typical) @ 5V
Standby Power 350mw; 70 mA (typical) @ 5V
Host System Interfaces Multi-Interface / Includes RS232 (TTL +5V, 4 Signals) / KBW / USB (HID Keyboard, Serial, IBM OEM); RS-232C (+/-12V) and IBM RS485 supported via adapter cable

Scan Performance

Scan Pattern Single scan line
Scan Angle Horizontal: 30°
Print Contrast 10% minimum reflectance difference
Pitch, Skew 60°, 60°
Decode Capabilities Reads standard 1D and GS1 DataBar symbologies
Warranty 5 year factory warranty

Environmental

Operating Temperature 0°C to 50°C (32°F to 122°F)
Storage Temperature -20°C to 60°C (-4°F to 140°F)
Humidity 0% to 95% non-condensing
Drop Designed to withstand 30 drops to concrete from 1.5 m
Environmental Sealing IP42
Light Levels 0 - 100,000 lux (direct sunlight)